


DISCOVER
THE FULL VALUE OF 4K
HIKVISION 4K SYSTEM

KEY FEATURES

■ Ultra-High Definition (UHD)

Until now, limited resolution has often hindered the accuracy of video analytics, mainly due to missing image details. Today, Hikvision's 4K system provides users incredibly clear and crisp images with increased quality and details, facilitating video content analytics and thus better use of video data.




■ 4K Output

Hikvision's 4K NVR is equipped with an HDMI 2.0 interface, transmitting video with 4K resolution and providing a more comprehensive solution than systems that are only able to provide 4K cameras or 4K codecs without the 4K output.



■ H.265+ Smart Codec

Hikvision 4K system incorporates H.265+ video compression, which allows users to more efficiently manage ultra-high definition video footage. Hikvision H.265+ improves the compression ratio with three key technologies – predictive encoding, noise suppression, and flexible bitrate control – reducing bandwidth and storage costs.



■ Full Smart Feature-set

As a part of Hikvision's smart product family, 4K products are equipped with features such as Smart Tracking, False Alarm Filtering, and smart detections including intrusion, line crossing, region entrance, region exit, and more.



APPLICATION SCENARIOS

The Hikvision 4K system will vastly improve applications in various scenarios such as city surveillance, stadiums, and parking lots, to name just a few, where clear, high-resolution images and intelligent surveillance are necessary. This is a system that includes a full set of 4K products versus a single 4K device. Hikvision leads the industry in offering a complete solution that allows 4K technology to be implemented in a variety of domains.



Parking lots



Cities



Stadiums

PRODUCT SHOWCASE



DS-2CD558560-IZS(H)
8 MP VF Dome Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps, MJPEG up to 1920 × 1080 @ 30 fps
- 2.8-12 mm motor-driven lens, 8-32 mm coming soon
- Color: 0.007 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- 3D DNR
- IR range up to 30 m
- 5 defined streams and up to 5 custom streams supported
- 6 behavior analyses, 3 exception detection, and face detection
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB
- Alarm I/O
- IP67, IK10



DS-2CD55C560-IZS(H)
12 MP IR VF Dome Network Camera

- 1/1.7" Progressive Scan CMOS
- 4000 × 3000 @ 20 fps
- 2.8-12 mm motor-driven lens
- Color: 0.008 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- Digital WDR
- 3D DNR
- IR range up to 30 m
- 5 defined streams and up to 5 custom streams supported
- 6 behavior analyses, 3 exception detection, and face detection
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB
- Alarm I/O, Audio I/O
- 12 VDC power output
- IP67, IK10



DS-2CD5A8560-IZS(H)
8 MP VF Bullet Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps, MJPEG up to 1920 × 1080 @ 30 fps
- 2.8-12 mm motor-driven lens, 8-32 mm coming soon
- Color: 0.007 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- 3D DNR
- IR range up to 50 m
- 5 defined streams and up to 5 custom streams supported
- 6 behavior analyses, 2 exception detection, and face detection
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB
- Alarm I/O
- IP67, IK10



DS-2CD5AC560-IZS(H)
12 MP IR VF Bullet Network Camera

- 1/1.7" Progressive Scan CMOS
- 4000 × 3000 @ 20 fps
- 2.8-12 mm motor-driven lens
- Color: 0.008 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- Digital WDR
- 3D DNR
- IR range up to 50 m
- 5 defined streams and up to 5 custom streams supported
- 6 behavior analyses, 2 exception detection, and face detection
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB
- Alarm I/O
- IP67, IK10



DS-2CD708560-(AP)
8 MP Box Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps
- Color: 0.007 lux @ (F1.2, AGC ON)
- Auto-iris, DC drive and P-iris optional
- Auto back focus (ABF) optional
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- Alarm I/O
- Audio I/O, mono sound
- High accuracy face detection and capture, which adopts new face detection, tracking and grading algorithms based on deep-learning technology
- Perimeter protection, based on deep learning powered target detection and classification algorithms, supports detection of line crossing, intrusion, region entrance, and region exit
- Five defined streams and up to five custom streams
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB



DS-2CD758560-IZ(H)S
8 MP IR Vari-Focal Dome Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps
- 2.8-12 mm motor-driven lens, 8-32 mm coming soon
- Color: 0.007 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- IR range up to 30 m
- Alarm I/O, Audio I/O
- IP67, IK10
- Anti-IR reflection
- High accuracy face detection and capture, which adopts new face detection, tracking and grading algorithms based on deep-learning technology
- Perimeter protection, based on deep learning powered target detection and classification algorithms, supports detection of line crossing, intrusion, region entrance, and region exit
- Five defined streams and up to five custom streams
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB



DS-2CD758560-IZ(H)S
8 MP IR Vari-Focal Dome Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps
- 2.8-12 mm motor-driven lens, 8-32 mm coming soon
- Color: 0.007 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- IR range: up to 50 m for 2.8-12 mm lens
- Alarm I/O
- IP67, IK10
- High accuracy face detection and capture, which adopts new face detection, tracking and grading algorithms based on deep-learning technology
- Perimeter protection, based on deep learning powered target detection and classification algorithms, supports detection of line crossing, intrusion, region entrance, and region exit
- Five defined streams and up to five custom streams
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB



DS-2CD7A8560-IZ(H)S
8 MP IR Vari-Focal Bullet Network Camera

- 1/1.8" Progressive Scan CMOS
- 3840 × 2160 @ 30 fps
- 2.8-12 mm motor-driven lens, 8-32 mm coming soon
- Color: 0.007 lux @ (F1.2, AGC ON)
- H.265, H.265+, H.264, H.264+
- 120 dB WDR
- IR range: up to 50 m for 2.8-12 mm lens
- Alarm I/O
- IP67, IK10
- High accuracy face detection and capture, which adopts new face detection, tracking and grading algorithms based on deep-learning technology
- Perimeter protection, based on deep learning powered target detection and classification algorithms, supports detection of line crossing, intrusion, region entrance, and region exit
- Five defined streams and up to five custom streams
- Built-in microSD/SDHC/SDXC card slot, up to 256 GB



DS-2DF8825IX-AEL(W)
DS-2DF8836IX-AEL(W)
DS-2DF8836I5X-AEL(W)
8 MP IR Network PTZ Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. Illumination:
Color: 0.005 lux @ (F1.5, AGC ON)
B/W: 0.0005 lux @ (F1.5, AGC ON)
- 25/36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, Smart IR
- 24 VAC & Hi-PoE
- Up to 200 m IR / 500 m Laser distance
- H.265+/H.265 video compression
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection
- Rapid focus
- IK10 IP67



DS-2DF6A825X-AEL
DS-2DF6A836X-AEL
8 MP Network PTZ Dome

- 2/3" progressive scan CMOS
- Up to 4096 × 2160 resolution
- Min. illumination:
Color: 0.005 lux @ (F1.5, AGC ON)
B/W: 0.0005 lux @ (F1.5, AGC ON)
- 25/36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, BLC, Optical Defog, EIS
- 24 VAC & Hi-PoE
- H.265+/H.265 video compression
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection
- IK10, IP67



DS-9600NI-I16(H)
DS-9600NI-I24(H)
Super I Series 4K NVR

- Up to 24 MP resolution recording
- H.265, H.265+, H.264, H.264+ video compression
- Dual HDMI output at up to 4K (3840 × 2160) resolution
- Up to 768 Mbps incoming bandwidth
- Up to 20-ch 1080p decoding capability
- Third-party network cameras supported
- RAID 0, 1, 5, 10 supported
- 4 Gigabit Ethernet interfaces



DS-9600NI-I8
DS-7700NI-I4(/16P)(B)
DS-7600NI-I2(/8/16P)
I Series 4K NVR

- Up to 12 MP resolution recording
- H.265, H.265+, H.264, H.264+ video compression
- HDMI output at up to 4K (3840 × 2160) resolution
- Up to 320 Mbps incoming bandwidth
- Up to 16-ch 1080p decoding capability
- Third-party network cameras supported
- RAID 0, 1, 5, 10 supported for the DS-9600NI-I8 models
- 4 Gigabit Ethernet interfaces



DISCOVER
THE FULL VALUE OF 4K
HIKVISION 4K SYSTEM

Distributed by



HIKVISION

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Germany
T +49-69-401507290
sales.adch@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +6-032-7224000
sales.my@hikvision.com

Hikvision Philippines
sales.ph@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

www.hikvision.com

Follow us on social media to get the latest product and solution information:

